



## SpiralVeyor® Print Finishing specification form

<b>Dimensions</b>	<p><b>PF</b></p> <p><b>PFeconomic</b> <b>PFcompact</b></p>	<b>PF</b>	<b>PFe</b>	<b>PFc</b>	
		<b>Belt width</b>	<b>16"</b>	<b>16"</b>	<b>16"</b>
		<b>Elevation</b>	<b>98"</b>	<b>98"</b>	<b>59"</b>
		<b>Foot print (Ød1)</b>	<b>88"</b>	<b>68"</b>	<b>68"</b>
		<b>Required belt length</b>	_____ ft.		
		<b>Top roller height (h3)*</b>	_____ ft./ inch		
		<b>Bottom roller height (h1)*</b>	_____ ft./ inch		
<b>Configurations:</b>					
<input type="checkbox"/> <b>A</b> <input type="checkbox"/> <b>B</b> <input type="checkbox"/> <b>C</b> <input type="checkbox"/> <b>D</b> <input type="checkbox"/> <b>E</b> <input type="checkbox"/> <b>F</b> <input type="checkbox"/> <b>G</b> <input type="checkbox"/> <b>H</b> <input type="checkbox"/> <b>L</b> <input type="checkbox"/> <b>R</b>					

<b>Application</b>	<b>Transport direction :</b>	<input type="checkbox"/> Up (TU)	<input type="checkbox"/> Down (TD)	<input type="checkbox"/> Belt speed __ m/min	
	<b>Use:</b>	<input type="checkbox"/> Cooling only	<input type="checkbox"/> Cooling and elevating	<input type="checkbox"/> Elevating only	<input type="checkbox"/> Other _____

<b>Product details</b>	<b>Products</b>	<b>Dimensions (L x W x H) (inch)</b>	<b>Leading side</b>	<b>Weight (per book)</b>	<b>Throughput (Nominal)</b>
	Minimum	_____ x _____ x _____	<input type="checkbox"/> short side <input type="checkbox"/> long side	_____ lbs	_____ / min
	Maximum	_____ x _____ x _____	<input type="checkbox"/> short side <input type="checkbox"/> long side	_____ lbs	_____ / min
	Average	_____ x _____ x _____	<input type="checkbox"/> short side <input type="checkbox"/> long side	_____ lbs	_____ / min

<b>Process details</b>			<b>Non-shingled</b>		<b>Shingled **</b>	
	<b>Max throughput</b>	<b>Required Drying time</b>	<b>Length A:</b>	<b>head to head</b>	<b>Length</b>	<b>Shingled overlap</b>
	_____ / hour	_____ sec	_____ inch	B: _____ inch	A: _____ inch	C _____ inch/%
	<b>Average throughput</b>	<b>Required Drying time</b>	<b>Length A:</b>	<b>head to head</b>	<b>Length</b>	<b>Shingled overlap</b>
	_____ / hour	_____ sec	_____ inch	B: _____ inch	A: _____ inch	C _____ inch/%
<b>Binder manufacturer</b>	<b>Binder type</b>	<b>Max. speed</b>		<b>Glue type(s)</b>		

\* The final heights of the top roller height h3 depend on bottom roller height h1 or visa versa and required belt length.

\*\* Shingled transport only at SpiralVeyor® PF.